



www.agbudget.co.uk Luxury Swimming Pool Kits & Equipment at Budget Prices

**Swimming Pool
Heat Pumps**

A red sunburst graphic above the text "Heat Seeker" in a grey, cursive font, all within a red-bordered frame.

Heat Seeker

**This heat pump comes with a 1 year warranty.
In addition there is a 2 year parts warranty on the compressor
and a 5 year parts warranty on the titanium heat exchanger.**

Ideal for domestic use between May and September using a solar or heat retention cover.



- *Remote digital Control Panel
- *Titanium Heat Exchanger
- *Suitable for Salt Water
- *Ecological Heating Method
- *High efficiency compressor
- *Self diagnostic
- *Fully programmable
- *Compact design
- *Outdoor Installation
- *Quick and easy installation
- *Strong steel casing
- *Very quiet operation
- *Reverse cycle defrost



HeatSeeker Swimming Pool Heat Pumps are manufactured by one of the largest Heat Pump companies in the world, with a proven reliability record stretching back over 15 years.

Technical Information

Code		WBR-5.6H-B	WBR-9.5H-B	WBR-12.5H-B
Rated Heating Capacity	W	5600	9500	12500
	BTU's/hr	19000	32500	42500
Input Power Heating	W	1160	1939	2550
Running Current Heating	A	3.6	8.8	11.6
COP	w/w	4.8	4.8	4.9
Power Supply	v/ph/hz	220/1/50		
Number of Compressors		1		
Compressor Type		Rotary		
Number of Fans		1		
Input Power of Fan	W	25	30	30
Fan Rotation Speed	rpm	950	950	950
Noise Level	dB	55	58	58
Water Connection	inches	1½	1½	1½
Water Flow Rate	m ³ /h	3 - 5	4 - 7	4 - 7
Water Pressure Drop	KPa	12	15	15
Unit Dimension	L	995	1085	1085
	W	360	370	370
	H	550	615	615
Packing Dimension	L	1090	1170	1170
	W	390	415	415
	H	580	645	645
Weight	Net	50	63	71
	Gross	53	67	75

This product is CE marked. The HeatSeeker heat pump is tested to current EN standards: EN 55014-1:2001, EN 55014-2:1997, EN 61000-3-2:2001 and EN 61000-3-3:1995.LVD: EN 60335-2-40:2003, EN 60335-1:2002.

Code		WBR-17.0H-A	WBR-21.0H-A-S
Rated Heating Capacity	W	17000	21000
	BTU's/hr	60000	73000
Input Power Heating	W	3500	4250
Running Current Heating	A	16.1	7.9
COP	w/w	4.8	4.9
Power Supply	v/ph/hz	220/1/50	
Number of Compressors		1	
Compressor Type		Rotary	Scroll
Number of Fans		1	
Input Power of Fan	W	200	200
Fan Rotation Speed	rpm	830	830
Noise Level	dB	60	60
Water Connection	inches	1½	1½
Water Flow Rate	m ³ /h	5 - 8	6 - 10
Water Pressure Drop	KPa	16	16
Unit Dimension	L	660	660
	W	660	660
	H	860	960
Packing Dimension	L	700	700
	W	740	740
	H	1010	1110
Weight	Net	108	111
	Gross	120	123